

## SPECIFICATIONS

Description	Solid Vinyl Floor Tile
Classification	ASTM F 1700 / Class III / Type B
Tile Sizes	24" x 24"
Thickness	3.0 mm (0.120")
Wear Layer Thickness	0.5 mm (0.020")
Critical Radiant Flux (ASTM E 648)	Class I rating
Smoke Density (ASTM E 662)	Pass
Dimensional Stability (ASTM F 2199)	Pass
Static Load Limit (ASTM F970)	Pass
Chemical Resistance (CNS 8907)	Pass
Light Resistance (CNS 8907)	Pass
Recycled Content of Backing	100%
Manufacturer's Warranty	10 year limited warranty

### Preparation & Installation

Refer to manufacturer's Installation Guidelines for proper preparation and installation information.

### EnviroStix® Self-Adhesive System

Adhesive	Solvent-free, Acrylic Dispersion
Thickness 0.23 mm	0.23 mm
Adhesive Carrier	Polyester Scrim
Covering Material	Brown Silicon Paper
Peeling Resistance	AFERA 4001 P11 30 N / 25 mm
Elongation at Break	DIN 53112
Tear Resistance	DIN 53112
Temperature Range	-30° up to 120° C
Condensation Water Resistance	Good
Aging Resistance	Very Good
Softener Resistance	Very Good
Adhesive Characteristics	Aggressively Adhesive

Highly resistant to plasticizer migration.