



FEATURES AND BENEFITS

- Allows for immediate access to foot traffic
- Pre-Cured no dry time
- Moisture Resistant
- Aggressive Bond Strength

DESCRIPTION:

TurboStix™ Plus is a pre-cured, double-sided adhesive tape for the rapid and permanent installation of a wide variety of resilient flooring types. TurboStix™ Plus has been designed specifically to provide instant bond and instant utilization for residential and commercial floor installations.

WHERE TO USE

- Approved for use with vinyl tile, vinyl plank, rubber flooring, carpet tiles, Carpet rolls, vinyl transition strips, rubber stair treads & risers, & other multi-use applications.
- Interior residential (rental apartments, condominiums and homes)
- Interior commercial (office buildings, retail spaces, hotel rooms, lobbies, convention centers, airports, hallways/ corridors, restaurant dining areas, and many other jobsite locations.)
- Interior institutional (Waiting areas, Hospitals, Medical offices, K-12, Higher Education, libraries and government buildings, etc.)

MIXING

- This product does not require mixing.

LIMITATIONS

- Interior installations only

- Do not install over any substrates containing asbestos.
- Install flooring only in areas recommended by the flooring manufacturer.
- Do not install in areas with known alkali silica reaction or osmotic blistering problems.
- Do not install over wet substrates with standing water.
- Do not install when the pH of the concrete slab is greater than or equal to 12 unless used with a Base King primer (ES-P or ES-MBP) or another PH Neutralizing primer.
- Do not install when the moisture vapor emission rate (MVER) and/or relative humidity (RH) of the concrete slab exceeds limitations set forth by your floor prep products and or flooring materials.
- See your flooring manufacturers installation and warranty limitations. Flooring manufactures recommendations supersede our own.

Available Roll Sizes & Coverage

TSP - 7 mil Roll Sizes	Coverage
36-inch x 100 linear feet	300 square feet
24-inch x 100 linear feet	200 square feet
6-inch x 100 linear feet	50 square feet
2-inch x 100 linear feet	16.67 square feet
For Custom Sizes see your Sales Rep	

SUITABLE SUBSTRATES

- Concrete (Must meet floor prep products and flooring manufacturers recommendations.)

- Exterior-grade plywood and other approved wood substrates (per flooring manufacturers' recommendations)
- High-moisture-rated cement self-leveling underlayments as well as patching and skim-coating compounds

SURFACE PREPARATION

- All substrates must be structurally sound, dry, solid, stable and smooth.
- The substrate should be completely clean and free of dust, dirt, oil, grease, paint, curing agents, concrete sealers, loosely bonded toppings, loose particles, and any other substance or condition that may prevent or reduce adhesion.
- Vacuum the surface with the brush attachment and then tack-mop the surface of the substrate using a damp mop to remove any remaining fines. Allow the surface to dry completely before installing TurboStix™ Plus.
- Concrete and cement-based underlayments/patches must be cured.
- See the floor prep products / flooring manufacturers guidelines for surface preparation requirements as well.

PRODUCT APPLICATION

(2-person Application recommended)

1. Mark layout lines before placing TurboStix™ Plus.
2. Mist the floor and 4 inches up the wall where your first roll will be installed.
3. One person holds roll to allow it to spin while the other places the TurboStix™ Plus roll into place, leaving 1-2 inches up the wall to trim off excess using a patch knife.
4. Carefully roll out material trying to avoid trapping any air bubbles, while smoothing out 24-36 inches at a time with a straight edge putty/ patch knife or similar tool.

5. When nearing the opposite wall mist the wall as before then roll out excess TurboStix™ Plus and cut it with a utility knife and press it into place.
6. For the next roll of TurboStix™ Plus follow previous instructions while butting it up tightly to the previously placed sheet. Do not overlap seams.
7. Continue to roll out and apply TurboStix™ Plus until the subfloor is completely covered.
8. Use your hands or roller, firmly press adhesive into the subfloor especially at all seams and edges.
9. Allow water to dry before removing any of the release liner.
10. Peel back enough of the release liner to expose the layout line.
11. Begin to place the flooring in line with the starter line and press into place while only removing release liner as needed. Follow flooring manufacturers installation instructions.

See the TurboStix™ Plus Double-Sided Adhesive Tape Application Instructions for full details on installation. For further questions on installing TurboStix™ Plus please call a member of our Base King, LLC Technical Team.

Product Characteristics

VOC's	0 g/l (out of 50 g/l)
Color	Clear w/ Scrim
Storage	10 Years
Storage Temps	(40° F -90° F) (4° C - 32° C)

Base King, LLC Manufacturer's Limited Warranty:

TurboStix™ Double Sided Multi-Use Adhesive Tape has a limited warranty to be free from manufacturing defects for a period of 90 days from the date of purchase. This warranty does not cover accidental damages, unreasonable or improper use, normal wear and tear, loss of use, or consequential damages. For additional warranty information please contact our office @ 706-278-2604. Open Mon-Thru 8am – 5pm & Fri 8am - 4pm. EST.