



FEATURES AND BENEFITS

- Allows for immediate access to foot traffic
- Pre-Cured no dry time
- Moisture Resistant
- Easily Repositioned
- Quick Repairs or Replacements

DESCRIPTION:

EZR™ is the newest addition of Base King primers. It is a pre-cured, double-sided adhesive tape for the fast and releasable installation carpet tiles with a wide variety of backing types. EZR™ has been designed specifically to provide immediate bond and instant utilization for commercial and/or residential floor installations. It was also designed to release from the floor easily to reposition and/or replace the flooring.

(See your sales associate with questions for use on specific materials.)

WHERE TO USE

- Interior Commercial or Residential Locations with suitable substrates. (Office, retail spaces, hotel rooms, lobbies, convention centers, airports, hallways/ corridors, dining areas, waiting areas, Hospitals, Medical offices, K-12, Higher Education, libraries and government buildings, etc.)

SUITABLE SUBSTRATES

- Concrete (Must meet floor prep products and flooring manufacturers recommendations.)
- Exterior-grade plywood and other approved wood substrates (per flooring manufacturers' recommendations)
- High-moisture-rated cement self-leveling underlayments as well as patching and skim-coating compounds

SURFACE PREPARATION

- All substrates must be structurally sound, dry, solid, stable and smooth.
- The substrate should be completely clean and free of dust, dirt, oil, grease, paint, curing agents, concrete sealers, loosely bonded toppings, loose particles, and any other substance or condition that may prevent or reduce adhesion.
- Vacuum the surface with the brush attachment and then tack-mop the surface of the substrate using a damp mop to remove any remaining fines. Allow the surface to dry completely before installing EZR™.
- Concrete and cement-based underlayments/patches must be cured.
- See the floor prep products / flooring manufacturers guidelines for surface preparation requirements as well.

LIMITATIONS

- Interior installations only
- Do not install over any substrates containing asbestos.
- Install flooring only in areas recommended by the flooring manufacturer.
- Do not install in areas with known alkali silica reaction or osmotic blistering problems.
- Do not install over wet substrates with standing water.
- Do not install when the pH of the concrete slab is greater than or equal to 12 unless used with an approved Base King PH neutralizing primer.
- Do not install when the moisture vapor emission rate (MVER) and/or relative humidity (RH) of the concrete slab exceeds limitations set forth by your floor prep products and or flooring materials.
- See your flooring manufacturers installation and warranty limitations. Flooring manufactures recommendations supersede EZR™ instructions.

Available Roll Sizes & Coverage

TSP - 7 mil Roll Sizes	Coverage
	25-foot minimum roll length
	Custom Widths cut to Order

PRODUCT APPLICATION

Each EZR™ System has their own set of installation instructions. See the EZR™ System Installation instructions available online or directly from you sales representative.

For further questions on installing EZR™ please call a member of our Base King, LLC Technical Team.

Product Characteristics

VOC's	0 g/l (out of 50 g/l)
Color	Clear w/ Scrim
Storage	10 Years
Storage Temps	(40° F -90° F) (4° C - 32° C)

Base King, LLC Manufacturer's Limited Warranty:

EZR™ Double Sided Multi-Use Adhesive Tape alone with no approved Base King, LLC primers has a limited warranty to be free from manufacturing defects for a period of 90 days from the date of purchase. This warranty does not cover accidental damages, unreasonable or improper use, normal wear and tear, loss of use, or consequential damages.

Other Warranties for EZR™ Systems with approved Base King, LLC primers are available online or at request from your sales rep. For additional warranty information please contact our office @ 706-278-2604. Open Mon-Thru 8am – 5pm & Fri 8am - 4pm. EST.